



Aluminiumgehäuse
Energieeffizienzklasse: IE1

Bestell-Nr.	Antriebsleistung in kW	Phasen / Pole	Spannung in Volt	Frequenz in Hz	Drehzahl in U/min	Baugröße	IE Klasse
720-050-01000	0,25	1Ph / 4P	230	50	1400	71A	IE1
720-050-01050	0,37	1Ph / 4P	230	50	1400	71B	IE1
720-050-01100	0,55	1Ph / 4P	230	50	1400	80A	IE1
720-050-01150	0,75	1Ph / 4P	230	50	1400	80B	IE1
720-050-01200	1,1	1Ph / 4P	230	50	1400	90S	IE1
720-050-01250	1,5	1Ph / 4P	230	50	1400	90L	IE1
720-050-01300	2,2	1Ph / 4P	230	50	1400	100L	IE1

Bestell-Nr.	A	AB	B	C	D	E	H	F	L	G	K	DH	M	N	P	HD	T	S
720-050-01000	112	145	90	45	14	30	71	5	250	11	7	M5x12	85	70	105	132	3,5	M6
720-050-01050	112	145	90	45	14	30	71	5	250	11	7	M5x12	85	70	105	132	3,5	M6
720-050-01100	125	160	100	50	19	40	80	6	295	15,5	10	M6x16	100	80	120	144	3,5	M6
720-050-01150	125	160	100	50	19	40	80	6	295	15,5	10	M6x16	100	80	120	144	3,5	M6
720-050-01200	140	180	100	56	24	50	90	8	335	20	10	M8x19	115	95	140	155	3,5	M8
720-050-01250	140	180	125	56	24	50	90	8	360	20	10	M8x19	115	95	140	155	3,5	M8
720-050-01300	160	205	140	63	28	60	100	8	380	24	12	M10x22	130	110	160	165	3,5	M8

