

	Bestell-Nr.			Technische Daten						Dimensionen					
Fördervolumen	rechtsdrehend	linksdrehend	P1 in bar	P2 in bar	P3 in bar	max. Dauerdrehzahl	max. intermittierende Drehzahl	min. Drehzahl	Sauganschluss 1	Druckanschluss 1	Druckanschluss 2	A in mm	B in mm	Gewicht in kg	
17,04	035-210-01000	035-210-01050	290	315	325	2500	3000	300	1/2"	1/2"	1/2"	168,5	119,5	11	
22,15	035-210-01100	035-210-01150	290	315	325	2500	3000	300	1/2"	1/2"	1/2"	172	121,5	11,5	
26,18	035-210-01200	035-210-01250	290	315	325	2500	3000	300	3/4"	1/2"	1/2"	174,5	124	12	
33,88	035-210-01300	035-210-01350	280	300	310	2200	2800	300	3/4"	3/4"	3/4"	179,5	125	13	
43,12	035-210-01400	035-210-01450	270	290	300	2000	2500	300	3/4"	3/4"	3/4"	185,5	130	13,5	
50,82	035-210-01500	035-210-01550	240	260	280	2000	2500	300	1"	3/4"	3/4"	190,5	130,5	14	
60,06	035-210-01600	035-210-01650	220	240	250	1800	2000	300	1"	3/4"	3/4"	196,5	136,5	14,5	
72,88	035-210-01700	035-210-01750	200	220	230	1600	1800	300	1"	3/4"	3/4"	204,5	135,5	15	
81,08	035-210-01800	035-210-01850	190	210	220	1500	1800	300	1-1/4"	3/4"	3/4"	209,5	140,5	15,5	
98,18	035-210-02000	035-210-02050	180	200	220	1500	1800	300	1-1/4"	1"	3/4"	226,5	154,5	15	
122,72	035-210-02100	035-210-02150	160	180	200	1500	1800	300	1-1/4"	1"	3/4"	242,5	158,5	17	

P1 = max. Dauerdruck (100%)

P2 = max. intermittierender Druck (max. 20 Sek.)

P3 = Spitzendruck (max. 6 Sek.)

