



Bestellnummer	Anschlussgröße	Einstellbereich in bar	Nomineller Volumenstrom	Material Körper	P max. Körper in bar	Leckage bei 80% des max. Einstellwertes in ccm/min	Maße Körper in mm											Maße Patrone in mm		Gewinde	Bohrungs-typ	
							A	B	C	E	F	G	H	I	L	M	Z	X	Y			
Aluminium Körper	231-950-01000	3/8"	5-60	60l/min	Alu	210	25	60,0	60,0	35,0	6,0	48,0	54,0	6,0	18,8	25,0	35,0	6,5	32,3	54,5	7/8-14 UNF	SAE10/2
	231-950-01050	3/8"	50-250	60l/min	Alu	210	25	60,0	60,0	35,0	6,0	48,0	54,0	6,0	18,8	25,0	35,0	6,5	32,3	54,5	7/8-14 UNF	SAE10/2
	231-950-01100	3/8"	150-350	60l/min	Alu	210	25	60,0	60,0	35,0	6,0	48,0	54,0	6,0	18,8	25,0	35,0	6,5	32,3	54,5	7/8-14 UNF	SAE10/2
	231-950-01150	1/2"	5-50	60l/min	Alu	210	25	60,0	60,0	35,0	6,0	48,0	54,0	6,0	18,8	25,0	35,0	6,5	32,3	54,5	7/8-14 UNF	SAE10/2
	231-950-01200	1/2"	50-250	60l/min	Alu	210	25	60,0	60,0	35,0	6,0	48,0	54,0	6,0	18,8	25,0	35,0	6,5	32,3	54,5	7/8-14 UNF	SAE10/2
	231-950-01250	1/2"	150-350	60l/min	Alu	210	25	60,0	60,0	35,0	6,0	48,0	54,0	6,0	18,8	25,0	35,0	6,5	32,3	54,5	7/8-14 UNF	SAE10/2
	231-950-01300	1/2"	5-50	100l/min	Alu	210	25	70,0	80,0	40,0	8,0	54,0	72,0	8,0	25,0	30,0	40,0	8,5	46,0	52,5	1 1/16-12 UNF	SAE12/2
	231-950-01350	1/2"	50-250	100l/min	Alu	210	25	70,0	80,0	40,0	8,0	54,0	72,0	8,0	25,0	30,0	40,0	8,5	46,0	52,5	1 1/16-12 UNF	SAE12/2
	231-950-01400	1/2"	150-350	100l/min	Alu	210	25	70,0	80,0	40,0	8,0	54,0	72,0	8,0	25,0	30,0	40,0	8,5	46,0	52,5	1 1/16-12 UNF	SAE12/2
	231-950-01450	3/4"	5-50	100l/min	Alu	210	25	70,0	90,0	40,0	8,0	54,0	82,0	8,0	25,0	30,0	40,0	8,5	46,0	52,5	1 1/16-12 UNF	SAE12/2
	231-950-01500	3/4"	50-250	100l/min	Alu	210	25	70,0	90,0	40,0	8,0	54,0	82,0	8,0	25,0	30,0	40,0	8,5	46,0	52,5	1 1/16-12 UNF	SAE12/2
	231-950-01550	3/4"	150-350	100l/min	Alu	210	25	70,0	90,0	40,0	8,0	54,0	82,0	8,0	25,0	30,0	40,0	8,5	46,0	52,5	1 1/16-12 UNF	SAE12/2
	231-950-01600	1"	5-50	180l/min	Alu	210	25	85,0	100,0	60,0	10,0	65,0	90,0	10,0	23,5	40,0	45,0	10,5	45,2	53,0	1 5/16-12 UNF	SAE16/2
	231-950-01650	1"	50-250	180l/min	Alu	210	25	85,0	100,0	60,0	10,0	65,0	90,0	10,0	23,5	40,0	45,0	10,5	45,2	53,0	1 5/16-12 UNF	SAE16/2
	231-950-01700	1"	150-350	180l/min	Alu	210	25	85,0	100,0	60,0	10,0	65,0	90,0	10,0	23,5	40,0	45,0	10,5	45,2	53,0	1 5/16-12 UNF	SAE16/2
	231-950-01750	1-1/4"	5-50	400l/min	Alu	210	100	100,0	100,0	60,0	10,0	80,0	90,0	10,0	25,0	45,0	55,0	10,5	45,2	49,8	1 5/16-12 UNF	SAE16/2
231-950-01800	1-1/4"	50-250	400l/min	Alu	210	100	100,0	100,0	60,0	10,0	80,0	90,0	10,0	25,0	45,0	55,0	10,5	45,2	49,8	1 5/16-12 UNF	SAE16/2	
231-950-01850	1-1/4"	150-350	400l/min	Alu	210	100	100,0	100,0	60,0	10,0	80,0	90,0	10,0	25,0	45,0	55,0	10,5	45,2	49,8	1 5/16-12 UNF	SAE16/2	
Stahl Körper	231-955-01000	3/8"	5-60	60l/min	Stahl	350	25	60,0	60,0	35,0	6,0	48,0	54,0	6,0	18,8	25,0	35,0	6,5	32,3	54,5	7/8-14 UNF	SAE10/2
	231-955-01050	3/8"	50-250	60l/min	Stahl	350	25	60,0	60,0	35,0	6,0	48,0	54,0	6,0	18,8	25,0	35,0	6,5	32,3	54,5	7/8-14 UNF	SAE10/2
	231-955-01100	3/8"	150-350	60l/min	Stahl	350	25	60,0	60,0	35,0	6,0	48,0	54,0	6,0	18,8	25,0	35,0	6,5	32,3	54,5	7/8-14 UNF	SAE10/2
	231-955-01150	1/2"	5-50	60l/min	Stahl	350	25	60,0	60,0	35,0	6,0	48,0	54,0	6,0	18,8	25,0	35,0	6,5	32,3	54,5	7/8-14 UNF	SAE10/2
	231-955-01200	1/2"	50-250	60l/min	Stahl	350	25	60,0	60,0	35,0	6,0	48,0	54,0	6,0	18,8	25,0	35,0	6,5	32,3	54,5	7/8-14 UNF	SAE10/2
	231-955-01250	1/2"	150-350	60l/min	Stahl	350	25	60,0	60,0	35,0	6,0	48,0	54,0	6,0	18,8	25,0	35,0	6,5	32,3	54,5	7/8-14 UNF	SAE10/2
	231-955-01300	1/2"	5-50	100l/min	Stahl	350	25	70,0	80,0	40,0	8,0	54,0	72,0	8,0	25,0	30,0	40,0	8,5	46,0	52,5	1 1/16-12 UNF	SAE12/2
	231-955-01350	1/2"	50-250	100l/min	Stahl	350	25	70,0	80,0	40,0	8,0	54,0	72,0	8,0	25,0	30,0	40,0	8,5	46,0	52,5	1 1/16-12 UNF	SAE12/2
	231-955-01400	1/2"	150-350	100l/min	Stahl	350	25	70,0	80,0	40,0	8,0	54,0	72,0	8,0	25,0	30,0	40,0	8,5	46,0	52,5	1 1/16-12 UNF	SAE12/2
	231-955-01450	3/4"	5-50	100l/min	Stahl	350	25	70,0	90,0	40,0	8,0	54,0	82,0	8,0	25,0	30,0	40,0	8,5	46,0	52,5	1 1/16-12 UNF	SAE12/2
	231-955-01500	3/4"	50-250	100l/min	Stahl	350	25	70,0	90,0	40,0	8,0	54,0	82,0	8,0	25,0	30,0	40,0	8,5	46,0	52,5	1 1/16-12 UNF	SAE12/2
	231-955-01550	3/4"	150-350	100l/min	Stahl	350	25	70,0	90,0	40,0	8,0	54,0	82,0	8,0	25,0	30,0	40,0	8,5	46,0	52,5	1 1/16-12 UNF	SAE12/2
	231-955-01600	1"	5-50	180l/min	Stahl	350	25	85,0	100,0	60,0	10,0	65,0	90,0	10,0	23,5	40,0	45,0	10,5	45,2	53,0	1 5/16-12 UNF	SAE16/2
	231-955-01650	1"	50-250	180l/min	Stahl	350	25	85,0	100,0	60,0	10,0	65,0	90,0	10,0	23,5	40,0	45,0	10,5	45,2	53,0	1 5/16-12 UNF	SAE16/2
	231-955-01700	1"	150-350	180l/min	Stahl	350	25	85,0	100,0	60,0	10,0	65,0	90,0	10,0	23,5	40,0	45,0	10,5	45,2	53,0	1 5/16-12 UNF	SAE16/2
	231-955-01750	1-1/4"	5-50	400l/min	Stahl	350	100	100,0	100,0	60,0	10,0	80,0	90,0	10,0	25,0	45,0	55,0	10,5	45,2	49,8	1 5/16-12 UNF	SAE16/2
231-955-01800	1-1/4"	50-250	400l/min	Stahl	350	100	100,0	100,0	60,0	10,0	80,0	90,0	10,0	25,0	45,0	55,0	10,5	45,2	49,8	1 5/16-12 UNF	SAE16/2	
231-955-01850	1-1/4"	150-350	400l/min	Stahl	350	100	100,0	100,0	60,0	10,0	80,0	90,0	10,0	25,0	45,0	55,0	10,5	45,2	49,8	1 5/16-12 UNF	SAE16/2	



Dauner Antriebstechnik GmbH  
 Industriestraße 3  
 96120 Bischberg - Trosdorf  
 Tel.: 095 03/5 00 08-0  
 Fax: 095 03/5 00 08-49  
 www.dauner-antriebstechnik.de

